

A two-stage algorithm for extracting the multiscale backbone of complex weighted networks

Paul B. Slater *

*University of California, Santa Barbara

Submitted to Proceedings of the National Academy of Sciences of the United States of America

The central problem of concern to Serrano, Boguñá and Vespignani [1] can be effectively and elegantly addressed using a well-established two-stage algorithm that has been applied to internal migration flows for numerous nations and several other forms of "transaction flow data" [2, 3, 4].

In the first stage, the N row and N column sums of the $N \times N$ matrix of weighted, directed network flows (f_{ij}) are alternately scaled to all equal 1, iteratively, until sufficient convergence to a *doubly*-stochastic table is attained. So doing serves as a control for multiscale effects. (This procedure—convergent under broad conditions [5]—leaves the cross-product ratios $\frac{f_{ij}f_{kl}}{f_{il}f_{kj}}$ [measures of association] invariant, and provides maximum-entropy estimates given the doubly-stochastic constraint. One may also consider for highly sparse networks, a preliminary smoothing of the matrix entries, or an adjustment of row and column sums to be proportional, not to 1, but to the number of non-zero entries in the row or column. Powering a doubly-stochastic matrix yields another [smoother] doubly-stochastic matrix.)

In the second stage of the algorithm, the N nodes (vertices) of the network are *hierarchically* clustered. One starts with an N -node graph with no links. Then, if the ij -entry of the doubly-standardized table is the greatest, a link is drawn from node i to node j , and so on, using the second, third... greatest links. Larger and larger strong components of the directed graph (digraph) emerge, until all the nodes are united

in a single strong component (that is, there exists a path of directed links from any node to any other). This final digraph (with links labeled by the original flow values) is an obvious candidate for the "multiscale backbone" of the complex weighted network. (In our recent study of migration between the 3,107 U. S. counties, this backbone consisted of 25,329 links [4]. In the methodology of Serrano, Boguñá and Vespignani [1], some of the N nodes may be omitted from the backbone, depending upon the significance level α employed, while the *single* strong component includes all N nodes. By stopping the hierarchical clustering before completion, however, in some suitable statistical manner, one might also isolate nodes.) An $O(M \log N)$ algorithm, where M is the number of edges of the network—developed by R. E. Tarjan—exists for the hierarchical clustering. If the digraph of the original network is not strongly connected, the sub-networks corresponding to its individual strong components can each be independently analyzed using the two-stage algorithm [5].

The two-stage procedure has proved effective—to use the internal migration context—in recognizing regional structures (such as the islands of Japan [2] and French Louisiana [4]) and in distinguishing "cosmopolitan" geographic units (such as Paris [3] and U. S. "Sunbelt" counties [4])—those with broad (hub-like or centralized) ties—from "provincial" units [2, 3, 4]. Graph-theoretic tests of an ordinal nature can be applied to assess the significance of the clusters found [4, sec. IV.B].

1. Serrano MA, Boguñá M, Vespignani A (2009) Extracting the multiscale backbone of complex weighted networks. *Proc Natl Acad Sci* 106:6483–6488.
2. Slater PB (1976) A hierarchical regionalization of Japanese prefectures using 1972 interprefectural migration flows. *Regional Stud* 10:123–132.
3. Slater PB (1976) Hierarchical internal migration regions of France. *IEEE Syst Man Cyb* 6:321–324.

4. Slater PB (2008) Hubs and clusters in the evolving United States internal migration network (<http://arxiv.org/abs/0809.2768>).
5. Hartfiel DF, Spellman JW (1972) A role for doubly stochastic matrices in graph theory. *Proc Amer Math Soc* 36:389–394.

Reserved for Publication Footnotes